

Product datasheet

Specifications



Mini Pragma surface enclosure - IP 40 - 1 x 18 modules - transparent door

13370

⚠ Discontinued on: 27-May-2019

⚠ Discontinued

Main

Range	Mini Pragma
Product Or Component Type	Enclosure
Enclosure Type	Modular enclosure
Nb Of 18 Mm Modules Per Row	18
Nb Of Horizontal Rows	1
Provided Equipment	1 marking kit 1 insulating plug 2 terminal block support 2 earth-neutral terminal blocks 16 holes
Type Of Door	Transparent
Width	364 mm
Height	221 mm
Depth	100 mm

Complementary

Enclosure Mounting	Surface
9 Mm Pitches	36
Total Number Of 18 Mm Modules	18
[In] Rated Current	63 A
[Ui] Rated Insulation Voltage	690 V
Type Of Rail	DIN
Number Of Terminal Blocks	2 neutral / earth (Quick) with 16 outgoing
Distribution Block Outgoers	16 x 10 mm ² for earth / neutral 16 x 16 mm ² for earth / neutral
Locking Options Description	Keylock option
Enclosure Material	Enclosure: self-extinguishing material
Colour	Enclosure: white (RAL 9003)

Environment

Standards	EN 60439-3 EN 50102 IEC 60695-2-1 IEC 60439-3 IEC 60529
-----------	---

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Fire Resistance	Back part: 650 °C conforming to IEC 60695-2-1 Front face: 650 °C conforming to IEC 60695-2-1
Ik Degree Of Protection	IK07 conforming to EN 50102

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.5 cm
Package 1 Width	22.7 cm
Package 1 Length	36.4 cm
Package 1 Weight	1.055 kg

Contractual warranty

Warranty	18 months
----------	-----------