

Product datasheet

Specifications



voltage release - MNx - 380..415 V AC

19062

⚠ Discontinued on: 31-Mar-2022

⚠ End-of-service on: 21-Nov-2020

⚠ Discontinued

Main

Range Of Product	Acti9
Product Or Component Type	Undervoltage release
Device Short Name	MNx
[Uc] Control Circuit Voltage	380...415 V AC 50/60 Hz
Control Type	Standard
9 Mm Pitches	4

Complementary

Range Compatibility	Acti 9 Acti9 NG125
[Ui] Rated Insulation Voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-5-1
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to EN/IEC 60947-5-1
Local Signalling	Action indicator
Mounting Mode	Fixed
Mounting Support	35 mm symmetrical DIN rail
Height	103 mm
Width	36 mm
Depth	69 mm
Electrical Durability	10000 cycles conforming to EN/IEC 60947-5-1
Connections - Terminals	Plate terminal - 1 cable(s) 2.5 mm² - flexible
Wire Stripping Length	10 mm
Tightening Torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Product Certifications	KEMA ASTA LCIE ASEFA
Ip Degree Of Protection	IP20 B conforming to EN/IEC 60947-5-1 IP4 conforming to EN/IEC 60947-5-1
Pollution Degree	3 conforming to EN/IEC 60947-5-1
Overvoltage Category	II

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative Humidity	95 % at 55 °C
Ambient Air Temperature For Operation	-25...60 °C
Ambient Air Temperature For Storage	-40...85 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8 cm
Package 1 Width	5.6 cm
Package 1 Length	11 cm
Package 1 Weight	0.2 kg

Contractual warranty

Warranty	18 months
----------	-----------