



PratiKa wander plug - straight -125 A - 2P + E - 200...250 V AC -**IP67**

81390

! Discontinued on: 03-Jul-2023

! Discontinued

Main

| Range | PratiKa |
|---------------------------|--------------|
| Product Or Component Type | Wander plug |
| Device Short Name | PratiKa plug |
| Plug, Socket Category | Low voltage |
| Poles Description | 2P + E |
| Network Type | AC |
| Outlet Standard | Industrial |

Complementary

| Plug, Socket, Control Station Shape | Straight |
|--|---|
| [In] Rated Current | 125 A |
| [Ue] Rated Operational Voltage | 200250 V |
| Network Frequency | 50/60 Hz |
| Ground Lug Clockwise Position | 6 h |
| Plug, Socket Material | Housing: self-extinguishing engineering polymer |
| Contacts Material | Pins: nickel plated brass |
| Connections - Terminals | Captive screws |
| Cable Cross Section | 1670 mm² |
| Cable Outer Diameter | 2648 mm |
| Cable Entry | Cable gland |
| Thread Type | Pg 48 |
| Net Weight | 1.18 kg |
| Height | 325 mm |
| Width | 131 mm |
| Depth | 131 mm |
| Colour | Grey (RAL 7035) |
| Voltage Colour | Blue |
| | |

Environment

Standards IEC 60309-1 IEC 60309-2

| Ip Degree Of Protection | IP67 conforming to IEC 60529 |
|---------------------------------------|---|
| Ik Degree Of Protection | IK08 conforming to EN 62262 |
| Fire Resistance | 850 °C conforming to IEC 60695-2-11 |
| Relative Humidity | 50 % at 40 °C 70 % at 30 °C 90 % at 20 °C |
| Operating Altitude | 2000 m |
| Ambient Air Temperature For Operation | 35 °C (86400 s) -2540 °C |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 12.9 cm |
| Package 1 Width | 12.9 cm |
| Package 1 Length | 30.6 cm |
| Package 1 Weight | 1.271 kg |
| Unit Type Of Package 2 | S03 |
| Number Of Units In Package 2 | 5 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 6.387 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Circularity Profile | No need of specific recycling operations |
|-----------------------|---|
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Eu Rohs Directive | Compliant with Exemptions |
| Reach Regulation | REACh Declaration |