



### Main

|                           |                |
|---------------------------|----------------|
| Range of product          | Harmony 9001SK |
| Product or component type | Pilot light    |
| Device short name         | 9001SK         |
| Lens type                 | Domed plastic  |
| Light block supply        | Direct         |

### Complementary

|   |  |
|---|--|
| Bezel material                              | Plastic  |
| Mounting diameter                           | 30 mm  |
| Shape of signaling unit head                | Round  |
| Cap/Operator or lens colour                 | Blue   |
| Light source                                | LED  |
| Bulb base                                   | BA 9s  |
| [Us] rated supply voltage                   | 120 V AC/DC  |
| Tightening torque                           | 0.8 N.m conforming to EN/IEC 60947-1   |
| Shape of screw head                         | Cross slotted head   |
| Connections - terminals                     | Screw clamp terminals (1 x 0.22...2 x 1.5 mm <sup>2</sup> ) conforming to EN/IEC 60947-1 |
| [Ith] conventional free air thermal current | 10 A   |
| Short-circuit protection                    | 10 A cartridge fuse conforming to EN/IEC 60947-5-1                                       |
| [Ui] rated insulation voltage               | 250 V (degree of pollution: 2) conforming to EN/IEC 60947-1                              |
| [Uimp] rated impulse withstand voltage      | 2.5 kV conforming to EN/IEC 60947-1  |
| Operating position                          | Any position   |
| CAD overall width                           | 54 mm  |
| CAD overall height                          | 70 mm  |
| CAD overall depth                           | 42 mm  |
| Product weight                              | 0.082 kg   |
| Device presentation                         | Complete product   |

### Environment

|                                   |                                  |
|-----------------------------------|----------------------------------|
| Electrical shock protection class | Class II conforming to IEC 61140 |
|-----------------------------------|----------------------------------|

|                                       |  |
|---------------------------------------|--|
| Protective treatment                  | TC   |
| IP degree of protection               | IP66 conforming to IEC 60529   |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 4X                               |
| Vibration resistance                  | 7 gn (f = 2...500 Hz) conforming to IEC 60068-2-6  |
| Shock resistance                      | 50 gn conforming to IEC 60068-2-27   |
| Ambient air temperature for operation | -25...70 °C  |
| Ambient air temperature for storage   | -40...70 °C  |
| Standards                             | EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>JIS C 4520<br>JIS C 852<br>UL 508<br>CSA C22.2 No 14 |
| Product certifications                | NEMA<br>UL 508   |

### Offer Sustainability

|                        |   |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 0921 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                  | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|