Product datasheet

Specifications





Push-button, Harmony 9001SK, plastic, mushroom 57mm, red, 30mm, spring return, 1 C/O

9001SKR25RH13

Main

Range Of Product	Harmony 9001SK
Product Or Component Type	Push-button
Device Short Name	9001SK
Type Of Operator	spring return
Operator Profile	Red mushroom Ø 57 mm, unmarked
Operator Additional Information	Screw-on plastic with set screw

Complementary

Complementary	
Bezel Material	Plastic
Mounting Diameter	30 mm
Cad Overall Width	46 mm
Cad Overall Height	45 mm
Cad Overall Depth	69 mm
Net Weight	0.102 kg
Operating Position	Any position
Shape Of Signaling Unit Head	Round
Contacts Type And Composition	1 C/O
Positive Opening	Without
Mechanical Durability	500000 cycles
Connections - Terminals	Screw clamp terminals, 1 x 0.222 x 1.5 mm ² conforming to EN/IEC 60947-1
Tightening Torque	0.8 N.m conforming to EN/IEC 60947-1
Shape Of Screw Head	Cross slotted
Contacts Material	Silver alloy contacts
Short-Circuit Protection	10 A cartridge fuse conforming to EN/IEC 60947-5-1
[Ith] Conventional Free Air Thermal Current	10 A
[Ui] Rated Insulation Voltage	250 V (pollution degree 3) conforming to EN/IEC 60947-1
[Uimp] Rated Impulse Withstand Voltage	2.5 kV conforming to EN/IEC 60947-1
[Ie] Rated Operational Current	3 A at 240 V, AC-15, A600-Q600 conforming to NEMA

0.55 A at 125 V, DC-13, A600-Q600 conforming to NEMA

[Icm] Rated Short-Circuit Making	12 kA at 600 V AC-15, 7200 VA
Capacity	15 kA at 480 V AC-15, 7200 VA
	30 kA at 240 V AC-15, 7200 VA
	60 kA at 120 V AC-15, 7200 VA
	0.1 kA at 600 V DC-13
	0.27 kA at 250 V DC-13
	0.55 kA at 125 V DC-13
Rated Breaking Capacity	3 kA at 240 V AC-15, 720 VA
	6 kA at 120 V AC-15, 720 VA
	1.2 kA at 600 V AC-15, 720 VA
	1.5 kA at 480 V AC-15, 720 VA
	0.1 kA at 600 V DC-13
	0.27 kA at 250 V DC-13
	0.55 kA at 125 V DC-13
Compatibility Code	9001SK
Device Presentation	Complete product
Cap/Operator Or Lens Colour	Red
Operator Profile	Mushroom Ø 57 mm
Type Of Operator	Spring return
Contacts Type And Composition	1 C/O
Size	30 mm

Environment

Protective Treatment	TC
Ambient Air Temperature For Storage	-4070 °C
Ambient Air Temperature For Operation	-2570 °C
Overvoltage Category	Class II conforming to IEC 61140
Ip Degree Of Protection	IP66 conforming to IEC 60529
Nema Degree Of Protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 4 NEMA 4
Standards	EN/IEC 60947-5-1 EN/IEC 60947-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 CSA C22.2 No 14
Product Certifications	NEMA UL 508
Vibration Resistance	7 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock Resistance	50 gn conforming to IEC 60068-2-27

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.9 cm
Package 1 Width	5.9 cm
Package 1 Length	9.401 cm

Package 1 Weight

108.862 g

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes


Certifications & Standards


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations

Product datasheet

Dimensions Drawings

Dimensions






e panel thickness: 1 to 6 mm / 0.04 to 0.24 in. a 28 mm / 1.10 in.

Mounting and Clearance

Contact Block Mounting Position

Top and Rear views



(1) It is possible to mount up to 3 levels of contacts blocks (maximum of 6 contacts blocks)

- (2) Operator
- (3) Locating notch

(4) Side 1

(5) Side 2