Product datasheet

Specifications





Miniature circuit breaker (MCB), Acti9 iK60N, 1P, 25A, C curve, 6000A (IEC/EN 60898-1)

A9K17125

Main

Wall		
Device Application	Distribution	
Range	Acti9	
Product Name	Acti9 iK60	
Product Or Component Type	Miniature circuit-breaker	
Device Short Name iK60N		
Poles Description	1P	
Number Of Protected Poles	1	
[In] Rated Current	25 A at 30 °C	
Network Type	AC	
Trip Unit Technology	Thermal-magnetic	
Curve Code	С	
Breaking Capacity	6000 A Icn at 230 V AC 50/60 Hz conforming to EN/IEC 60898-1	
Suitability For Isolation	Yes conforming to EN/IEC 60898-1	
Standards	EN/IEC 60898-1	
Product Certifications	AENOR	

Complementary

Network Frequency	50/60 Hz	
Magnetic Tripping Limit	510 x ln	
[Ics] Rated Service Breaking Capacity	6000 A 100 % conforming to EN/IEC 60898-1 - 230 V AC 50/60 Hz	
Limitation Class	3 conforming to EN/IEC 60898-1	
[Ui] Rated Insulation Voltage	440 V AC 50/60 Hz conforming to EN/IEC 60898-1	
[Uimp] Rated Impulse Withstand Voltage	tand 4 kV conforming to EN/IEC 60898-1	
Control Type	Toggle	
Local Signalling	ON/OFF indication	
Mounting Mode	Clip-on	
Mounting Support	DIN rail	
9 Mm Pitches	es 2	
Height	85 mm	
Width	18 mm	

Depth	78.5 mm	
Net Weight	100 g	
Colour	White	
Mechanical Durability	20000 cycles	
Electrical Durability	10000 cycles	
Locking Options Description	Padlocking device	
Connections - Terminals	Tunnel type terminal (top or bottom) 125 mm² rigid Tunnel type terminal (top or bottom) 116 mm² flexible	
Wire Stripping Length	14 mm for top or bottom connection	
Tightening Torque	2 N.m top or bottom	
Earth-Leakage Protection	Without	

Environment

Ip Degree Of Protection	IP20 conforming to IEC 60529
Pollution Degree	2 conforming to EN/IEC 60898-1
Overvoltage Category	111
Ambient Air Temperature For Operation	-2560 °C
Ambient Air Temperature For Storage	-4085 °C

Packing Units

PCE
-
1
7.3 cm
1.8 cm
8.5 cm
101.0 g
BB1
12
8.1 cm
9.8 cm
22.4 cm
1.257 kg
\$03
132
30.0 cm
30.0 cm
40.0 cm
14.315 kg

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations