Product datasheet

Specifications





Contactor, TeSys Deca, 4P(4NO), AC-1, <=440V, 200A, 230V AC 50Hz coil, screw clamp terminals

LC1D115004P5

Main

Range TeSys Range Of Product TeSys Deca Product Or Component Type Contactor Device Short Name LC1D Contactor Application Resistive load Utilisation Category AC-1 AC-3 AC-3e AC-4 Poles Description 4P [Ue] Rated Operational Voltage Power circuit: <= 1000 V AC 25400 Hz Power circuit: <= 460 V DC		
Product Or Component Type Contactor Device Short Name LC1D Contactor Application Resistive load Utilisation Category AC-1 AC-3 AC-3e AC-4 Poles Description 4P [Ue] Rated Operational Voltage Power circuit: <= 1000 V AC 25400 Hz Power circuit: <= 460 V DC [le] Rated Operational Current 200 A (at <60 °C) at <= 440 V AC AC-1 for power circuit	Range	TeSys
Device Short Name LC1D Contactor Application Resistive load Utilisation Category AC-1 AC-3 AC-3e AC-4 Poles Description 4P [Ue] Rated Operational Voltage Power circuit: <= 1000 V AC 25400 Hz Power circuit: <= 460 V DC [le] Rated Operational Current 200 A (at <60 °C) at <= 440 V AC AC-1 for power circuit	Range Of Product	TeSys Deca
Contactor Application Resistive load Utilisation Category AC-1 AC-3 AC-3e AC-4 Poles Description 4P [Ue] Rated Operational Voltage Power circuit: <= 1000 V AC 25400 Hz Power circuit: <= 460 V DC	Product Or Component Type	Contactor
Utilisation Category AC-1 AC-3 AC-3e AC-4 Poles Description 4P [Ue] Rated Operational Voltage Power circuit: <= 1000 V AC 25400 Hz Power circuit: <= 460 V DC	Device Short Name	LC1D
AC-3 AC-3e AC-4 Poles Description 4P [Ue] Rated Operational Voltage Power circuit: <= 1000 V AC 25400 Hz Power circuit: <= 460 V DC	Contactor Application	Resistive load
[Ue] Rated Operational Voltage Power circuit: <= 1000 V AC 25400 Hz	Utilisation Category	AC-3 AC-3e
Power circuit: <= 460 V DC	Poles Description	4P
	[Ue] Rated Operational Voltage	
[Uc] Control Circuit Voltage 230 V AC 50 Hz	[Ie] Rated Operational Current	200 A (at <60 °C) at <= 440 V AC AC-1 for power circuit
	[Uc] Control Circuit Voltage	230 V AC 50 Hz

Complementary

Compatibility Code	LC1D
Pole Contact Composition	4 NO
Protective Cover	With
[Ith] Conventional Free Air Thermal Current	200 A (at 60 °C) for power circuit
Irms Rated Making Capacity	1260 A at 440 V for power circuit conforming to IEC 60947
Rated Breaking Capacity	1100 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	250 A 40 °C - 10 min for power circuit 550 A 40 °C - 1 min for power circuit 950 A 40 °C - 10 s for power circuit 1100 A 40 °C - 1 s for power circuit
Associated Fuse Rating	250 A gG at <= 690 V coordination type 1 for power circuit 200 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	0.6 mOhm - Ith 200 A 50 Hz for power circuit
Power Dissipation Per Pole	24 W AC-1
[Ui] Rated Insulation Voltage	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Power circuit: 1000 V conforming to IEC 60947-4-1
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to IEC 60947

Safety Reliability Level	B10d = 684932 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 10000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical Durability	8 Mcycles
Electrical Durability	0.8 Mcycles 200 A AC-1 at Ue <= 440 V
Control Circuit Type	AC at 50 Hz
Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	0.30.6 Uc (-4070 °C):drop-out AC 50 Hz 0.851.1 Uc (-4055 °C):operational AC 50 Hz 11.1 Uc (5570 °C):operational AC 50 Hz
Inrush Power In Va	300 VA 50 Hz cos phi 0.8 (at 20 °C)
Hold-In Power Consumption In Va	22 VA 50 Hz cos phi 0.3 (at 20 °C)
Heat Dissipation	38 W at 50 Hz
Operating Time	620 ms opening 2050 ms closing
Maximum Operating Rate	2400 cyc/h 60 °C
Connections - Terminals	Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 12.5 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 12.5 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 12.5 mm ² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: solid without cable end Power circuit: connector 1 10120 mm ² - cable stiffness: flexible without cable end Power circuit: connector 2 1050 mm ² - cable stiffness: flexible without cable end Power circuit: connector 2 1050 mm ² - cable stiffness: flexible with cable end Power circuit: connector 2 1050 mm ² - cable stiffness: flexible with cable end Power circuit: connector 2 1050 mm ² - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm ² - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm ² - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm ² - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm ² - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm ² - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm ² - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm ² - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm ² - cable stiffness: solid without cable end
Tightening Torque	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
Mounting Support	Plate Rail

Environment

Standards CSA C22.2 No 14 EN 60947-4-1 EN 60947-4-1 EN 60947-5-1 IEC 60947-5-1 IEC 60947-5-1 UL 508 Product Certifications CCC GOST GL RINA LROS (Lloyds register of shipping) UL BV DNV CSA	
Product Certifications CCC GOST GL RINA LROS (Lloyds register of shipping) UL BV DNV	
GL RINA LROS (Lloyds register of shipping) UL BV DNV	
LROS (Lloyds register of shipping) UL BV DNV	
UL BV DNV	
UL BV DNV	
DNV	
CSA	
UKCA	
Ip Degree Of Protection IP20 front face conforming to IEC 60529	
Protective Treatment TH conforming to IEC 60068-2-30	

Climatic Withstand	conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat
Permissible Ambient Air Temperature Around The Device	-4060 °C 6070 °C with derating
Operating Altitude	03000 m
Fire Resistance	850 °C conforming to IEC 60695-2-1
Flame Retardance	V1 conforming to UL 94
Mechanical Robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms) Shocks contactor open (6 Gn for 11 ms)
Height	158 mm
Width	150 mm
Depth	132 mm
Net Weight	2.86 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	19.0 cm
Package 1 Width	20.5 cm
Package 1 Length	21.0 cm
Package 1 Weight	2.969 kg

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information