Product datasheet

Specifications





(!) Discontinued

TeSys Deca contactor , 4P(4 NO) , AC-1 , <= 440V, 200A , 72V DC standard coil

LC1D115004SD

- () Discontinued on: 10-Oct-2020
- (!) End-of-service on: 04-Nov-2020

Main

in an i	
Range	TeSys
Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LC1D
Contactor Application	Resistive load
Utilisation Category	AC-1 AC-3 AC-3e AC-4
Poles Description	4P
[Ue] Rated Operational Voltage	Power circuit: <= 1000 V AC 25400 Hz Power circuit: <= 460 V DC
[le] Rated Operational Current	200 A (at <60 °C) at <= 440 V AC AC-1 for power circuit
[Uc] Control Circuit Voltage	72 V DC

Complementary

· · · · · · · · · · · · · · · · · ·	
Compatibility Code	LC1D
Pole Contact Composition	4 NO
Contact Compatibility	M8
Protective Cover	With
[Ith] Conventional Free Air Thermal Current	200 A (at 60 °C) for power circuit
Irms Rated Making Capacity	1260 A at 440 V for power circuit conforming to IEC 60947
Rated Breaking Capacity	1100 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	250 A 40 °C - 10 min for power circuit 550 A 40 °C - 1 min for power circuit 950 A 40 °C - 10 s for power circuit 1100 A 40 °C - 1 s for power circuit
Associated Fuse Rating	250 A gG at <= 690 V coordination type 1 for power circuit 200 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	0.6 mOhm - Ith 200 A 50 Hz for power circuit
Power Dissipation Per Pole	24 W AC-1
[Ui] Rated Insulation Voltage	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Power circuit: 1000 V conforming to IEC 60947-4-1

Overvoltage Category	Ш
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to IEC 60947
Safety Reliability Level	B10d = 684932 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 10000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical Durability	8 Mcycles
Electrical Durability	0.8 Mcycles 200 A AC-1 at Ue <= 440 V
Control Circuit Type	DC standard
Coil Technology	With integral suppression device
Control Circuit Voltage Limits	0.751.2 Uc (-4055 °C):operational DC 0.150.4 Uc (-4070 °C):drop-out DC 11.2 Uc (5570 °C):operational DC
Inrush Power In W	270365 W (at 20 °C)
Hold-In Power Consumption In W	2.45.1 W at 20 °C
Operating Time	2035 ms closing 4075 ms opening
Time Constant	25 ms
Maximum Operating Rate	1200 cyc/h 60 °C
Connections - Terminals	Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 12.5 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 12.5 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 12.5 mm ² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: solid without cable end Power circuit: connector 1 10120 mm ² - cable stiffness: flexible without cable end Power circuit: connector 1 10120 mm ² - cable stiffness: flexible without cable end Power circuit: connector 1 10120 mm ² - cable stiffness: flexible without cable end Power circuit: connector 1 10120 mm ² - cable stiffness: flexible with cable end Power circuit: connector 1 10120 mm ² - cable stiffness: flexible with cable end Power circuit: connector 1 10120 mm ² - cable stiffness: solid without cable end Power circuit: connector 1 10120 mm ² - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm ² - cable stiffness: solid without cable end Power circuit: connector 1 10120 mm ² - cable stiffness: solid without cable end Power circuit: connector 1 10120 mm ² - cable stiffness: solid without cable end Power circuit: connector 1 10120 mm ² - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm ² - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm ² - cable stiffness: solid without cable end
Tightening Torque	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector hexagonal screw head 4 mm
Mounting Support	Rail Plate
Environment	
Standards	CSA C22 2 No 14

Standards	CSA C22.2 No 14
	EN 60947-4-1
	EN 60947-5-1
	IEC 60947-4-1
	IEC 60947-5-1
	UL 508
Product Certifications	RINA
	CCC
	BV
	CSA
	GL
	DNV
	UL
	GOST
	LROS (Lloyds register of shipping)

Ip Degree Of Protection	IP20 front face conforming to IEC 60529
Protective Treatment	TH conforming to IEC 60068-2-30
Climatic Withstand	conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat
Permissible Ambient Air Temperature Around The Device	-4060 °C 6070 °C with derating
Operating Altitude	03000 m
Fire Resistance	850 °C conforming to IEC 60695-2-1
Flame Retardance	V1 conforming to UL 94
Mechanical Robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms) Shocks contactor open (6 Gn for 11 ms)
Height	158 mm
Width	150 mm
Depth	132 mm
Net Weight	2.86 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	16.8 cm
Package 1 Width	21.2 cm
Package 1 Length	18.5 cm
Package 1 Weight	2.75 kg

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information