# **Product datasheet**

Specifications





# Contactor, TeSys Deca, 4P(4NO), AC-1, 440V, 200A, 240V AC 50/60Hz coil,screw clamp terminals

LC1D115004U7

#### Main

Range	TeSys
Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LC1D
Contactor Application	Resistive load
Utilisation Category	AC-1 AC-3 AC-3e AC-4
Poles Description	4P
[Ue] Rated Operational Voltage	Power circuit: <= 1000 V AC 25400 Hz Power circuit: <= 460 V DC
[Ie] Rated Operational Current	200 A (at <60 °C) at <= 440 V AC AC-1 for power circuit
[Uc] Control Circuit Voltage	240 V AC 50/60 Hz

### Complementary

Compatibility Code	LC1D
Pole Contact Composition	4 NO
Protective Cover	With
[Ith] Conventional Free Air Thermal Current	200 A (at 60 °C) for power circuit
Irms Rated Making Capacity	1260 A at 440 V for power circuit conforming to IEC 60947
Rated Breaking Capacity	1100 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	250 A 40 °C - 10 min for power circuit 550 A 40 °C - 1 min for power circuit 950 A 40 °C - 10 s for power circuit 1100 A 40 °C - 1 s for power circuit
Associated Fuse Rating	250 A gG at <= 690 V coordination type 1 for power circuit 200 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	0.6 mOhm - Ith 200 A 50 Hz for power circuit
Power Dissipation Per Pole	24 W AC-1
[Ui] Rated Insulation Voltage	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Power circuit: 1000 V conforming to IEC 60947-4-1
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to IEC 60947

Safety Reliability Level	B10d = 684932 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 10000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical Durability	8 Mcycles
Electrical Durability	0.8 Mcycles 200 A AC-1 at Ue <= 440 V
Control Circuit Type	AC at 50/60 Hz
Coil Technology	Built-in bidirectional peak limiting diode suppressor
Control Circuit Voltage Limits	0.30.5 Uc (-4070 °C):drop-out AC 50/60 Hz 0.81.15 Uc (-4055 °C):operational AC 50/60 Hz 11.15 Uc (5570 °C):operational AC 50/60 Hz
Inrush Power In Va	280350 VA 60 Hz cos phi 0.8 (at 20 °C) 280350 VA 50 Hz cos phi 0.8 (at 20 °C)
Hold-In Power Consumption In Va	218 VA 60 Hz cos phi 0.3 (at 20 °C) 218 VA 50 Hz cos phi 0.3 (at 20 °C)
Heat Dissipation	38 W at 50/60 Hz
Operating Time	620 ms opening 2050 ms closing
Maximum Operating Rate	2400 cyc/h 60 °C
Connections - Terminals	Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 12.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 12.5 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: connector 1 10120 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: connector 2 1050 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: connector 2 1050 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: connector 1 10120 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: connector 1 10120 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: connector 2 1050 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: connector 2 1050 mm <sup>2</sup> - cable stiffness: solid without cable end
Tightening Torque	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
Mounting Support	Plate

### Environment

Standards	004.000.011-44
Standards	CSA C22.2 No 14
	EN 60947-4-1
	EN 60947-5-1
	IEC 60947-4-1
	IEC 60947-5-1
	UL 508
Product Certifications	UL
	CSA
	GOST
	RINA
	BV
	GL
	LROS (Lloyds register of shipping)
	DNV
	000
	UKCA

Ip Degree Of Protection

IP20 front face conforming to IEC 60529

Protective Treatment	TH conforming to IEC 60068-2-30	
Climatic Withstand	conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat	
Permissible Ambient Air Temperature Around The Device	-4060 °C 6070 °C with derating	
Operating Altitude	03000 m	
Fire Resistance	850 °C conforming to IEC 60695-2-1	
Flame Retardance	V1 conforming to UL 94	
Mechanical Robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms) Shocks contactor open (6 Gn for 11 ms)	
Height	158 mm	
Width	150 mm	
Depth	132 mm	
Net Weight	2.86 kg	

# **Packing Units**

Unit Type Of Package 1	PCE
	FUL
Number Of Units In Package 1	1
Package 1 Height	19.000 cm
Package 1 Width	20.600 cm
Package 1 Length	20.900 cm
Package 1 Weight	2.960 kg
Unit Type Of Package 2	\$04
Number Of Units In Package 2	4
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	12.340 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	16
Package 3 Height	75.000 cm
Package 3 Width	80.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	54.520 kg

### **Contractual warranty**

Warranty

18 months

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information