# **Product datasheet**

Specification





# TeSys F reversing contactor - 3P(3 NO) AC-3 <= 440 V 115 A 220 V AC 40...400 Hz

LC2F115M7

! Discontinued on: 31-Dec-2023

! Discontinued

#### Main

wain	
Range	TeSys
Product Name	TeSys F
Product Or Component Type	Reversing contactor
Device Short Name	LC2F
Contactor Application	Resistive load
	Motor control
Utilisation Category	AC-3
ounsation dategory	AC-3 AC-1
Device Presentation	Preassembled with reversing power busbar
Poles Description	3P
Power Pole Contact Composition	3 NO
[Ue] Rated Operational Voltage	<= 1000 V AC 50/60 Hz
	<= 460 V DC
[le] Rated Operational Current	115 A (at <40 °C) at <= 440 V AC AC-3
[10] Natou Operational Current	200 A (at <40 °C) at <= 440 V AC AC-1
Motor Power Kw	EE IAM at 200 400 V AC E0/00 I I
Motor Fower Rw	55 kW at 380400 V AC 50/60 Hz 59 kW at 415 V AC 50/60 Hz
	59 kW at 440 V AC 50/60 Hz
	65 kW at 1000 V AC 50/60 Hz
	75 kW at 500 V AC 50/60 Hz
	30 kW at 220240 V AC 50/60 Hz
	80 kW at 660690 V AC 50/60 Hz
Control Circuit Type	AC at 40400 Hz
[Uc] Control Circuit Voltage	220 V AC 40400 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
Overvoltage Category	III
[Ith] Conventional Free Air Thermal Current	200 A (at 40 °C)
Irms Rated Making Capacity	1150 A AC conforming to IEC 60947-4-1
Rated Breaking Capacity	920 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	1100 A 40 °C - 10 s
	640 A 40 °C - 30 s
	520 A 40 °C - 1 min
	400 A 40 °C - 3 min
	320 A 40 °C - 10 min
Associated Fuse Rating	125 A aM at <= 440 V
-	200 A gG at <= 440 V
Average Impedance	0.37 mOhm - Ith 200 A 50 Hz

[Ui] Rated Insulation Voltage	1000 V conforming to IEC 60947-4-1 1500 V conforming to VDE 0110 group C
Power Dissipation Per Pole	5 W AC-3
Interlocking Type	Mechanical
Mounting Support	Plate
Standards	EN 60947-1 JIS C8201-4-1 EN 60947-4-1 IEC 60947-4-1 IEC 60947-1
Product Certifications	ABS UL RMRoS CB RINA LROS (Lloyds register of shipping) CCC CSA DNV UKCA
Connections - Terminals	Power circuit: lugs-ring terminals 1 cable(s) 95 mm²  Power circuit: connector 1 cable(s) 95 mm²  Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm²flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²solid without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm²solid without cable end Power circuit: bar 2 cable(s) - busbar cross section: 20 x 3 mm
Tightening Torque	Power circuit: 10 N.m Control circuit: 1.2 N.m
Operating Time	2335 ms closing 515 ms opening
Mechanical Durability	10 Mcycles
Maximum Operating Rate	2400 cyc/h 55 °C
Complementary	
Control Circuit Voltage Limits	Operational: 0.851.1 Uc at 50/60 Hz (at <55 °C) Drop-out: 0.20.55 Uc at 50/60 Hz (at <55 °C)
Inrush Power In Va	550 VA 50 Hz cos phi 0.3 (at 20 °C) 660 VA 60 Hz cos phi 0.3 (at 20 °C)
Hold-In Power Consumption In Va	45 VA 50 Hz cos phi 0.3 (at 20 °C) 55 VA 60 Hz cos phi 0.3 (at 20 °C)
Heat Dissipation	1216 W
Environment	
Ip Degree Of Protection	IP20 front face with shrouds conforming to IEC 60529 IP20 front face with shrouds conforming to VDE 0106
Protective Treatment	тн
Ambient Air Temperature For Operation	-555 °C
Ambient Air Temperature For Storage	-6080 °C
Permissible Ambient Air Temperature Around The Device	-4070 °C

3000 m without derating

Operating Altitude

Mechanical Robustness	Vibrations contactor open: 2 Gn, 5300 Hz Vibrations contactor closed: 6 Gn, 5300 Hz Shocks contactor open: 9 Gn for 11 ms Shocks contactor closed: 15 Gn for 11 ms
Height	162 mm
Width	345 mm
Depth	171 mm
Net Weight	6.86 kg

#### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	22.5 cm
Package 1 Width	36.0 cm
Package 1 Length	53.0 cm
Package 1 Weight	9.55 kg

## **Contractual warranty**

Warranty 18 months

### Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information