# **Product datasheet**

Specification





### Contactor, TeSys K, 3P, AC-3/ AC-3e, 440V, 6A, 1NC aux, 24V DC coil,faston connectors

LP1K06015BD

### Main

Range	TeSys
Product Or Component Type	Contactor
Device Short Name	LP1K
Contactor Application	Motor control

Utilisation Category	AC-3	
Junisation Category	AC-3 AC-3e	
	AC-4	
Poles Description	3P	
	37	
Power Pole Contact Composition	3 NO	
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC <= 400 Hz	
	Signalling circuit: <= 690 V AC <= 400 Hz	
[le] Rated Operational Current	6 A (at <60 °C) at <= 440 V AC AC-3 for power circuit	
	6 A (at <60 °C) at <= 440 V AC AC-3e for power circuit	
Control Circuit Type	DC standard	
[Uc] Control Circuit Voltage	24 V DC	
Motor Power Kw	1.5 kW at 220230 V AC 50/60 Hz AC-3	
	2.2 kW at 380415 V AC 50/60 Hz AC-3	
	3 kW at 440/690 V AC 50/60 Hz AC-3	
	1.5 kW at 220230 V AC 50/60 Hz AC-3e	
	2.2 kW at 380415 V AC 50/60 Hz AC-3e	
	3 kW at 440/690 V AC 50/60 Hz AC-3e	
	1.5 kW at 220230 V AC 50/60 Hz AC-4	
	2.2 kW at 380415 V AC 50/60 Hz AC-4	
	3 kW at 440/690 V AC 50/60 Hz AC-4	
Auxiliary Contact Composition	1 NC	
[Uimp] Rated Impulse Withstand Voltage	8 kV	
Overvoltage Category	III	
[Ith] Conventional Free Air	20 A (at 60 °C) for power circuit	
Thermal Current	10 A (at 50 °C) for signalling circuit	
Irms Rated Making Capacity	110 A AC for power circuit conforming to IEC 60947	
	110 A AC for signalling circuit conforming to IEC 60947	
Rated Breaking Capacity	110 A at 220230 V conforming to IEC 60947	
<b>0</b> , <i>y</i>	110 A at 380400 V conforming to IEC 60947	
	110 A at 415 V conforming to IEC 60947	
	110 A at 440 V conforming to IEC 60947	
	80 A at 500 V conforming to IEC 60947	

25-Apr-2024 Life Is On Schneider

[Icw] Rated Short-Time Withstand Current	90 A 50 °C - 1 s for power circuit 85 A 50 °C - 5 s for power circuit
	80 A 50 °C - 10 s for power circuit
	60 A 50 °C - 30 s for power circuit
	45 A 50 °C - 1 min for power circuit
	40 A 50 °C - 3 min for power circuit
	20 A 50 °C - >= 15 min for power circuit
	80 A - 1 s for signalling circuit
	90 A - 500 ms for signalling circuit
	110 A - 100 ms for signalling circuit
Associated Fuse Rating	25 A gG at <= 440 V for power circuit
	25 A aM for power circuit
	10 A gG for signalling circuit conforming to IEC 60947
	10 A gG for signalling circuit conforming to VDE 0660
Average Impedance	3 mOhm - Ith 20 A 50 Hz for power circuit
[Ui] Rated Insulation Voltage	Power circuit: 600 V conforming to UL 508
	Power circuit: 690 V conforming to IEC 60947-4-1
	Signalling circuit: 690 V conforming to IEC 60947-4-1
	Signalling circuit: 690 V conforming to IEC 60947-5-1
	Signalling circuit: 600 V conforming to UL 508
	Power circuit: 600 V conforming to CSA C22.2 No 14
	Signalling circuit: 600 V conforming to CSA C22.2 No 14
Insulation Resistance	> 10 MOhm for signalling circuit
Inrush Power In W	3 W (at 20 °C)
Hold-In Power Consumption In W	3 W at 20 °C
Heat Dissipation	1.3 W
Control Circuit Voltage Limits	Operational: 0.81.15 Uc (at <50 °C) Drop-out: >= 0.10 Uc (at <50 °C)
Connections - Terminals	Solder pins (external diameter: 0.035 mm)
Maximum Operating Rate	3600 cyc/h
Auxiliary Contacts Type	type instantaneous 1 NC
Minimum Switching Current	5 mA for signalling circuit
Minimum Switching Voltage	17 V for signalling circuit
Mounting Support	Printed circuit boards
Operating Time	3040 ms coil energisation and NO closing
. •	10 ms coil de-energisation and NO opening
Safety Reliability Level	P10d = 1360963 avalog contactor with naminal load conforming to EN/ISO 13940 1
Salety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1
	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical Durability	10 Mcycles
Electrical Durability	1.3 Mcycles 6 A AC-3 at Ue <= 440 V
2.00th loar Darability	•
	1.3 Mcycles 6 A AC-3e at Ue <= 440 V 0.05 Mcycles 36 A AC-4 at Ue <= 440 V
Height	58 mm
Width	45 mm
Depth	57 mm
Net Weight	0.225 kg
	··g

### **Environment**

Standards EN/IEC 60947-4-1
EN/IEC 60947-5-1
UL 60947-4-1
UL 60947-5-1
CSA C22.2 No 60947-4

CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4

Product Certifications	CB Scheme CCC UL CSA EAC CE
Ip Degree Of Protection	IP2X
Ambient Air Temperature For Operation	-2550 °C
Ambient Air Temperature For Storage	-5080 °C
Operating Altitude	2000 m without derating
Flame Retardance	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102

## **Packing Units**

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.800 cm
Package 1 Width	6.200 cm
Package 1 Length	6.500 cm
Package 1 Weight	244.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	50
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	12.460 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	800
Package 3 Height	75.000 cm
Package 3 Width	80.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	207.360 kg

### **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>②</b>	Reach Free Of Svhc	
<b>9</b>	Toxic Heavy Metal Free	
<b>②</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information