

TeSys - LT3TK Thermal time delay protection relay 48 V

LT3TK048

! Discontinued on: 31-Dec-2023

! Discontinued

Main

Range Of The Product	TeSys
Device Short Name	LT3TK
Product Or Component Type	Relay
Device Application	Protection
Relay Application	Time delay relay

Complementary

[Us] Rated Supply Voltage	48 V AC/DC		
Voltage Range	0.851.1 Us		
Contacts Type And Composition	2 C/O multi voltage		
[Ithe] Conventional Enclosed Thermal Current	5 A		
Ambient Air Temperature For Operation	-2560 °C		
Control Type	Automatic reset Manual reset		
Hold-In Power Consumption In W	5679 W		
Height	85 mm		
Width	81 mm		
Depth	80 mm		

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.0 cm
Package 1 Width	13.5 cm
Package 1 Length	13.5 cm
Package 1 Weight	476.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	3
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm

Package 2 Weight

1.897 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
Ø	Mercury Free	
⊘	Rohs Exemption Information	Yes
Rea	ch Regulation	REACh Declaration
Eu f	Rohs Directive	Compliant EU RoHS Declaration
Chir	na Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Wee	e	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins