

residual current circuit-breaker -NeoBreak - 2P - 25 A - 300 mA -240/415 V

NBKRB225300CA

! Discontinued on: 01-Mar-2019

! Discontinued

### Main

Product Or Component Type	Residual current circuit breaker
Range Of Product	NeoBreak
Device Short Name	NBKRB
Poles Description	2P
[In] Rated Current	25 A
9 Mm Pitches	2
Quantity Per Set	1 piece

## Complementary

Network Frequency	50 Hz
[Ue] Rated Operational Voltage	240/415 V
[Ui] Rated Insulation Voltage	440 V
[Uimp] Rated Impulse Withstand Voltage	4 kV
Height	81 mm
Width	36 mm
Depth	49 mm
Electrical Durability	5000 cycles

### **Environment**

Standards	IS 12640
Ambient Air Temperature For Operation	-540 °C

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.6 cm
Package 1 Width	3.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	0.184 ka

# **Contractual warranty**

Warranty

18 months

## Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive	Not applicable, out of EU RoHS legal scope
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins