



120mm Rotating Mirror Blue 24VAC-DC

XVR12B06

Main

| Range Of Product | Harmony XVR |
|---------------------------|---------------------------------|
| Product Or Component Type | Prewired rotating mirror beacon |
| Sound Signalling | Without |
| Device Short Name | XVR |
| Mounting Diameter | 120 mm |
| Ip Degree Of Protection | IP23 conforming to IEC 60529 |
| [Us] Rated Supply Voltage | 24 V AC/DC |
| Light Source | High luminosity LED, blue |

Complementary

| Material | ABS (acrylonitrile butadiene-styrene): body part AS: globe |
|--|--|
| Cad Overall Width | 120 mm |
| Cad Overall Depth | 120 mm |
| Net Weight | 0.5 kg |
| Marking | CE |
| Product Mounting | By 3 M5 screws |
| Supply Voltage Limits | 1930 V DC 21.626.4 V AC |
| [Uimp] Rated Impulse Withstand Voltage | 0.8 kV |
| Current Consumption | 125 mA |
| Flashing Frequency | 2.3 Hz |
| Clamping Connection Capacity | 0.83 mm² |
| Awg Gauge | AWG 18 |
| Cable Length | 400 mm |

Environment

| Standards | IEC 61000-6-2 IEC 61000-6-4 |
|---------------------------------------|----------------------------------|
| Protective Treatment | TC |
| Ambient Air Temperature For Storage | -3570 °C |
| Ambient Air Temperature For Operation | -1050 °C |
| Electrical Shock Protection Class | Class II conforming to IEC 61140 |

Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 14 cm |
| Package 1 Width | 14.2 cm |
| Package 1 Length | 19.5 cm |
| Package 1 Weight | 634 g |
| Unit Type Of Package 2 | S04 |
| Number Of Units In Package 2 | 8 |
| Package 2 Height | 30 cm |
| Package 2 Width | 40 cm |
| Package 2 Length | 60 cm |
| Package 2 Weight | 6.477 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Rohs Exemption Information

Certifications & Standards


| Reach Regulation | REACh Declaration |
|--------------------------|--|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |


XVR12B06

Dimensions Drawings

Rotating Mirror Beacon

Dimensions





Product datasheet

XVR12B06

Mounting and Clearance

Rotating Mirror Beacon

Panel Cut-out

