

# Product datasheet

Specifications



## 1 tone siren - 106 dB - 24 V AC DC

XVSB1

! Discontinued on: 01-Nov-2020

! Discontinued

### Main

Range Of Product	Harmony XVS Application
Product Or Component Type	Siren
Device Short Name	XVS
Signalling Type	1 tone siren
[Us] Rated Supply Voltage	24 V AC/DC
Noise Level	106 dB
Cable End Type	With cable end

### Complementary

Material	Butadiene styrene acrylic: cone Glass reinforced polyamide 6: body
Net Weight	0.86 kg
Operating Position	Any position
[Ui] Rated Insulation Voltage	250 V conforming to EN/IEC 60947-1
[Uimp] Rated Impulse Withstand Voltage	1.5 kV conforming to EN/IEC 60947-1
Current Consumption	440 mA
Sound Frequency	1000 Hz +/- 10 %
Clamping Connection Capacity	<= 1 x 1.5 mm <sup>2</sup>
Cable Entry	1 tapped entry for cable gland (included) for Pg 7

### Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1
Protective Treatment	TC
Ambient Air Temperature For Storage	-40...70 °C
Ambient Air Temperature For Operation	-40...50 °C
Electrical Shock Protection Class	Class III conforming to EN/IEC 61140
Ip Degree Of Protection	IP40

### Contractual warranty

Warranty	18 months
----------	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

