

# Product datasheet

Specifications



## 2 tones siren - 106 dB - 230 V AC

XVSM2

⚠ Discontinued on: 01-Nov-2020

⚠ Discontinued

### Main

Range Of Product	Harmony XVS Application
Product Or Component Type	Siren
Device Short Name	XVS
Signalling Type	2 tones siren
[Us] Rated Supply Voltage	230 V AC
Noise Level	106 dB
Cable End Type	With cable end

### Complementary

Material	Butadiene styrene acrylic: cone Glass reinforced polyamide 6: body
Net Weight	0.86 kg
Operating Position	Any position
[Ui] Rated Insulation Voltage	250 V conforming to EN/IEC 60947-1
[Uimp] Rated Impulse Withstand Voltage	4 kV conforming to EN/IEC 60947-1
Current Consumption	55 mA
Sound Frequency	700 Hz +/- 15 % 800 Hz +/- 15 %
Clamping Connection Capacity	<= 1 x 1.5 mm²
Cable Entry	1 tapped entry for cable gland (included) for Pg 7

### Environment

Standards	EN/IEC 60947-5-1 EN/IEC 60947-1
Protective Treatment	TC
Ambient Air Temperature For Storage	-40...70 °C
Ambient Air Temperature For Operation	-40...50 °C
Electrical Shock Protection Class	Class II conforming to EN/IEC 61140
Ip Degree Of Protection	IP40

### Contractual warranty

Warranty	18 months
----------	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

